

Smart FV Charger



- Easily integrated into solar storage system
- Compatible with ALL brand EVs
- Charge EVs with renewable energy
- Smart load balancing working mode

Model	FCharger-7KS	FCharger-11KT	FCharger-22KT
AC Power supply	1P+N+PE	3P+N+PE	
Rated Power	7.4kW	11kW	22kW
Rated Voltage	AC 230V, 50/60Hz	AC 400V, 50/60Hz	
Rated Current	32A	16A	32A
Display Screen	3.8-inch LCD screen		
Indicator Light	4 LED lights		
Safety Protection	Over current protection, over voltage protection, under voltage protection, over temperature protection, leakage protection, unconnected PE ground protection etc.		
RCD	TypeA(30mA)+DC 6mA built-in		
Altitude	2000m		
Storage temperature	-40~75°C		
Operation temperature	-30~50°C		
Relative humidity	95%RH, No water droplet condensation		
Vibration	0.5G, No acute vibration and impaction		
Installation location	Indoor or outdoor, good ventilation, no flammable, explosive		
Mounting	Wall-mounted or pole-mounted(mounting pole is optional)		
Product size (H*W*D)	388.45*202.45*96mm	388.45*202.45*107.26mm	
Product Weight (NW)	2.4kg	3.8kg	5kg